

Hersteller	Schließkraft	Holmabstand	min. Einbauhöhe	max. Einbauhöhe	Öffnungsweg	Zentrierring Ø Auswerferseite	Zentrierring Ø Düsenseite	Düse gerade	Düse mit Radius	Gewinde Auswerferstange
Arburg	35 t	220 x 220 mm	150	300	60-200	110	110	X		M 12
Demag	50 t	355 x 355 mm	210	450	400	125	125	X		M 12
Demag	50 t	355 x 355 mm	210	450	400	125	125	X		M 12
Demag	50 t	355 x 355 mm	210	450	400	125	125	X		M 12
Demag	50 t	355 x 355 mm	210	450	400	125	125	X		M 12
Demag	80 t	400 x 400 mm	250	450	450	125	125	X		M12
Engel	80 t	350 x 350 mm	150	430	310	125	125	X		M 12
Demag	125 t	475 x 450 mm	230	460	450	125	125	X		M 16
Demag	150 t	500 x 500 mm	250	560	500	160	160	X		M 16
KM	150 t	500 x 500 mm	300	600	600	125	125	X		M 16
Demag	200 t	580 x 580 mm	340	690	575	160	160	X		M 16
Demag	200 t	560 x 560 mm	310	660	575	160	160	X		M 16
Demag	250 t 2K	630 x 630 mm	310	830	675	125	125	X		M 16
Demag	330 t	710 x 630 mm	330	710	675	200	200	X		M 16
Haitian	530 t	840 x 830 mm	350	850	850	200	200	X		M 16
Demag	650 t	1000 x 900 mm	450	950	930	125	125	X		M 16